

# Featured Article: Best Practices for Very Large Boundary Surveys—Coordinate Reference Systems

By Landon Blake

Revised On 2017-03-26

In this article we are going to discuss best practices for selecting and using coordinate reference systems on very large boundary surveys. (For a reminder of our definition for very large boundary surveys, see the featured article entitled "10 Best Practices for Very Large Boundary Surveys".)

## What is a coordinate reference system?

We will provide a very simple definition of coordinate reference system that will serve us for the remainder of this article: A coordinate reference system is used to identify the position of geographic features.

In the case of a very large boundary survey, we use coordinate reference systems to identify the position of property corners, property corner monuments, and other elements of our boundary survey. In most cases, we will be using a coordinate reference system that includes a map projection. A map projection is a geometric construct used to "project" the location of features on the curved surface of the Earth onto a plane, or flat surface that is more useful for mapping.

Why is it important to think about the coordinate reference system used for your very large boundary survey?

## Article Summary

In this article, we look at best practices for the selection and management of a coordinate reference system on very large boundary surveys. We define the term "coordinate reference system", identify two problems related to coordinate reference systems on large boundary surveys and look at four (4) best practices. These best practices are:

- 1) Know how your measurements are affected.
- 2) Know how big is big enough to matter.
- 3) Select an appropriate coordinate reference system.
- 4) Include appropriate coordinate reference system information on your boundary survey map.

Featured Article: Best Practices for Very Large Boundary Surveys—Coordinate Reference Systems

By Landon Blake

Revised On 2017-03-26

It is important to consider the coordinate reference system for your very large boundary system for two (2) reasons:

- Over large areas, the shape of the earth distorts your surveying measurements and calculations.
- The distortions that impact your measurements and calculations can result in the improper location of property corners and boundaries.

Consider the following four (4) best practices for selecting and using a coordinate reference system for your very large boundary survey.

Best Practice #1: Know how your measurements are affected.

On a very large boundary survey, you need to understand how the shape of the earth, and your use of a coordinate reference system, can impact your measurements and calculations. This distortion can occur in at least four (4) ways:

- **Distortion of distances.**

Distances can be shorter or longer on the grid or plane used in many map projections. A scale factor is used to convert distances between the grid or plane and "ground," or the earth's surface. The scale factor used can vary with the location and elevation of the project. Significant change in elevation within a project can also distort distances.

## Why Is A CRS Important On A Very Large Boundary Survey?

In a very large boundary survey, the coordinate reference system we select will control the coordinate values of points and lines in our survey. This includes the property corner points and boundary segments of the surveyed parcels. These elements of the boundary survey are warped in one way or another by the coordinate reference system.

- **Distortions of directions and angles.**

Directions and angles can also be distorted by the shape of the earth over large areas. Meridians converge as you move towards the poles, spherical excess results in the misclosure of large traverses, and lines on the latitudinal curve have a constantly changing bearing.

- **Distortions of the area.**

Areas of parcels are also distorted over large areas and in the use of map projections. Like distances, areas can be larger or smaller on the grid or plane, depending on the parcel location and the type of projection used.

- **Distortions in shape.**

The shapes of parcels and lines can also be distorted over large areas, and in the use of map projections.

## **Best Practice #2: Know How Big is Big Enough to Matter**

The four (4) types of distortions listed above will not be significant in all boundary surveys. One task for the boundary survey is to understand when the errors are big enough to matter. The following characteristics of your very large boundary survey can impact the size of the distortions:

- The size (area) of the very large boundary survey.
- The size (length) of the very large boundary survey.
- The location of the very large boundary survey about

"On a very large boundary survey, you need to understand how the shape of the Earth, and your use of a coordinate reference system, can impact your measurements and calculations."

## Featured Article: Best Practices for Very Large Boundary Surveys—Coordinate Reference Systems

By Landon Blake

Revised On 2017-03-26

the coordinate reference system.

- The type of coordinate reference system (and map projection) selected for the very large boundary survey.
- The elevation of points in the very large boundary survey.

Consider some brief examples:

- The larger the area of a very large boundary survey, the greater the spherical excess.
- As the distance increases between your very large boundary survey and elements of the map projection, the angular distortions (mapping angle) and scale factor distortions increase.
- Scale factor or the difference between grid distances and ground distances can increase with elevation.

### **Best Practice #3: Select an appropriate CRS for your very large boundary survey.**

It is important to select the appropriate coordinate reference system for your very large boundary survey. Many surveyors choose to work on their local state plane coordinate system. Almost all boundary surveys at the surveying company I work for are done on state plane coordinates. However, I know I'm guilty of using the state plane coordinate system by default. Don't make this

same mistake.

Understand how your particular state plane coordinate system distorts measurements and make a good professional judgment on whether it is the best choice for the very large boundary survey under consideration. You can view a list of map projection types from the USGS at <http://egsc.usgs.gov/isb/pubs/MapProjections/projections.html>.

What are some factors you may want to consider when selecting a coordinate reference system for your very large boundary survey? They include the following:

- **The elements for which you want to minimize distortion on your survey.**

These are the elements listed in Best Practice #1. For example: If doing large scale work for a tax assessment, it may be more important to minimize errors to an area than the other elements.

- **The shape and alignment of your project.**

For example, Some map projections work well for projects with a large east-west extent, while others work better for projects with a large north-south extent.

- **The location of your project within the map projection used by your CRS.**

If your CRS uses a map projection that places your project location near the edge, or across the edge, of a

"Understand how your particular state plane coordinate system distorts measurements and make a good professional judgment on whether it is the best choice for your very large boundary survey."

map projection zone, it may be a poor choice.

- **Your ability to perform calculations that move between your surveyed positions on the surface of the earth and the map projection plane or grid.**

For example, NGS makes available software online that can be used to convert between latitude/longitude positions and state plane coordinates.

- **Local laws and regulations may require the use of specific coordinate reference systems for specific types of projects.**

For example, Many jurisdictions now require boundary surveys to be referenced to the state plane coordinate system.

### **Best Practice #4: Include appropriate coordinate reference system data on your filed survey.**

In many jurisdictions, you are required by law to file a survey in the public record if your survey hits certain triggers. It is important to include detailed information about the coordinate reference system used for your survey, especially if coordinate values are shown. (I provide coordinate values on all of the property corner monuments shown on my filed surveys.) This allows retracing surveyors to understand how your work was completed and preserves the value of the work that is reflected on your filed survey map.

"It is important to include detailed information about your coordinate reference system used on your survey on you boundary survey map, especially if coordinate values are shown. This allows retracing surveyors to understand how your work was completed and preserves the value of the work that is reflected on your map."

## Featured Article: Best Practices for Very Large Boundary Surveys—Coordinate Reference Systems

By Landon Blake

Revised On 2017-03-26

What information needs to be shown the coordinate reference system you selected for your very large boundary survey? It should show, at a minimum, the following elements:

- The identity (name) of the coordinate reference system.
- The identity (name) of the horizontal and vertical datum used in the coordinate reference system.
- The scale factor used to move distances and areas between the surface of the earth and the plane (or grid).
- The mapping angle used to move directions and angles between the surface of the earth and the plane (or grid).
- Identity (name) and published coordinates for the control points used to establish the coordinate reference system for the very large boundary survey.

Remember that some jurisdictions have requirements you must meet to you use certain coordinate reference systems, or if you use them in a particular way. For example, California requires that you show ties to control monuments and other information on your filed survey map if you show California state plane coordinates. You have to meet additional requirements if you list accuracies for these coordinates.

### Special CRS Considerations For Very Large Boundary Surveys On the PLSS

There are a couple of special considerations when selecting a CRS for very large boundary surveys on the Public Land Survey System.

The first consideration has to do with the basis-of-bearing for the original GLO surveys on the PLSS. The basis-of-bearing for these surveys was typically astronomic north. Although the direction of due north established from GNSS-derived longitude pairs will be close to astronomic north, it won't be exactly the same. This difference is because of small distortions caused by the deflection of the vertical, or plumb line.

Even more importantly, astronomic north can be very different from grid north in a state plane coordinate system or other map projection. (For more

Featured Article: Best Practices for Very Large Boundary Surveys—Coordinate Reference Systems

By Landon Blake

Revised On 2017-03-26

## Conclusion

I'm certainly not a geodesist. There is a great deal I still have to learn about geodesy and its application to land surveying. Many boundary surveyors share that challenge with me. However, especially when working on very large boundary surveys, knowledge of geodesy and coordinate reference systems becomes more important. Hopefully, this article will get some of my readers to think about the issues involved, and to learn more, as I plan to do.

information see the article entitled "The Double Proportion Made Complex".)

A second consideration has to do with the scale factor used for the original GLO surveys. These surveys were measured on a ground system, not grid system, at the surface of the actual terrain. If you don't think about this and blindly apply a scale factor from your coordinate reference system, you are going to mess up some distance measurements.

There are other geodetic quirks of the PLSS, like the survey of the latitudinal curve on baselines. Select your CRS for surveys on the PLSS with appropriate care and forethought.